

Item Number
RAM-VB-106R4

RAM No-Drill™ Seat Bases

National Products, Inc.

Vehicle base for the Dodge Sprinter (2003-Newer) Buick Rendezvous (2004-Newer)

SPECIFICATIONS

Placement

Passenger side on the floor, under the seat

Drilling Required

No - uses existing seat bolts

Seat Configuration

Bucket

Construction/Finish

Steel/Black Powdercoat

Pole or Pedestal

Purchased Separately

Weight

9.5 lbs.

Features

Installs in minutes with no drilling required
Angled step moves pole away from passenger leg space

Misc.

Rugged lifetime warranty construction



Shown In Use
For Buick Rendezvous



Shown In Use
For Dodge Sprinter



RAM-VB-106R4
For Buick Rendezvous



RAM-VB-106R4
For Dodge Sprinter

National Products, Inc.
Phone: 206-763-8361
Fax: 206-763-9615
Address: 1205 S Orr St
Seattle, WA 98108
Website: www.ram-mount.com
Email: staff@ram-mount.com



Item Number
RAM-VB-106R4

RAM No-Drill™ Seat Bases
National Products, Inc.

Vehicle base for the
Dodge Sprinter (2003-Newer)
Buick Rendezvous (2004-Newer)

INSTALLATION INSTRUCTIONS FOR DODGE SPRINTER

1. Move the passenger seat to the rearmost setting.
2. Remove the front two seat rail bolts, loosen the back four seat bolts, that fasten the passenger seat brackets to the vehicle floor.
3. Without moving the seat, place the base over the front of the seat bracket.
4. Re-install the seat bolts.
5. Attach the RAM-VB-SB4 riser to base with the provided carriage bolts, washers, and nuts.

INSTALLATION INSTRUCTIONS FOR BUICK RENDEZVOUS

1. Attach the riser included in your kit to the No-Drill™ base and set aside.
2. Move the passenger side seat to its most forward position.
3. Using an 18MM socket, loosen the two rear nuts holding the passenger seat frame to the floor board. Loosen them until the top of the nut is flush with the top of the bolt.
4. Move the passenger side seat all the way back. Using the 18MM socket, remove the two nuts holding the front of the seat frame to the floor board. Once these are removed, gently lift the front of the seat off the floor.
5. Place the base in between the floor and seat frame, over the floor studs. Use the two slots that are passing in the same direction. The mounting platform with riser should be near the center console area.
6. Lower seat back over the studs and re-tighten the two nuts previously removed.
7. Move the seat as far forward as the mount will allow and re-tighten the two rear seat frame nuts.
8. Move the seat back to a normal or comfortable location.

Please note that once installed, some seat travel may be limited due to the position of the riser. Be careful when adjusting the seat to avoid being pinched between the seat lever and riser.

National Products, Inc.
Phone: 206-763-8361
Fax: 206-763-9615
Address: 1205 S Orr St
Seattle, WA 98108
Website: www.ram-mount.com
Email: staff@ram-mount.com

